

Stock Axminster Specification

Carpet Width	0.61m or 0.914m
Construction	Traditional Woven Axminster
Yarn	Dewsbury 3/37's
Pile Content	80% Wool, 20% Nylon
Weft	Jute or Polypropylene
Warp	Polyester
Backing	Fray Resistant Latex Compound
Quality Name	Bronze 3/37's
Quality Row	6
Pitch	7
BS ISO 8543 Total Mass	2518 g/m ²
Total Mass	74 oz/yd ²
Total Pile Mass	1119 g/m ²
Total Pile Mass	33.0 oz/yd ²
BS ISO 8543 Surface Pile Mass	886 g/m ²
ISO 1765 Total Thickness	11mm
BS ISO 1766 Surface Pile Thickness	7mm
BS ISO 8543 Surface Pile Density	0.12 g/cm ³
ISO 1763 Number of tufts/loops	23.6
S (per 100mm)	27.6
G (per 100mm) Nz/dm ²	651
Luxury Class (EN 1307:2005)	4

E.U Standards

Class 33 - Commercial General (EN 1307:2005)



Castor Chair Suitability - Rating A: Continuous use (EN 1307:2005)



Light Fastness (EN 1307:2005)



Slip Resistance No Performance Determined (EN 14041:2005)



Formaldehyde Emission - Classed With Testing (EN 14041:2005)



Resistance to Fraying (EN 1307)



Reaction to Fire: Bfl - s1 (EN 13501-1:2002)



Luxury Class 4 (EN 1307:2005)



All specifications subject to normal manufacturing tolerances. Production dye can vary in colour from batch to batch. Cut-pile carpets, may show shading/pile reversal.